

Hosketts Lane, Neather Wallop – Ford signage plans

ALL SIGNS TO BE SET 450mm from edge of carriageway

Location 1

Install 1 X FORD sign (FIG 554 @ 600mm) and 1 X 350 Yards plate (FIG 572 with X-height of 62.5mm) on new post for Eastbound traffic. Bottom of distance plate must be 2.4m above verge.

Install on new 4m post with concrete footing.



Location 2

Install 1 X FORD sign (FIG 554 @ 600mm) and 1 X 350 Yards plate (FIG 572 with X-height of 62.5mm) in direction of Ford.

Install 1 X TRY YOUR BRAKES sign (FIG 554.1 @ 600mm) for traffic having passed through the ford.

Bottom of signs to be 2.4m above verge.

Install on new 4m post with concrete footing.



Location 3

Move 'ICE' warning sign from location 5 and re-erect here. Bottom of sign must be 2.4m above verge height.

Install on new 4m post with concrete footing.



Location 4

Move 'ICE' warning sign from location 6 and re-erect here.

Take up and dispose of existing width restriction sign and post.

Install 1 X '2.0m – 6'6" @ 750mm diameter.

Bottom of width restriction sign should be 2.4m above verge.

Install both signs for traffic travelling towards Ford on new 5m post with concrete footing.



Location 5

Remove ICE warning sign to store on site for use at location 3 and dispose of existing post.



Location 6

Remove ICE warning sign to store on site for use at location 4 and dispose of existing post.



Location 7

Install 1 X TRY YOUR BRAKES sign (FIG 554.1 @ 600mm) on reverse of this sign for traffic having passed through the ford.

